


ARTIC 700



Characteristics

Structure	White or Stainless steel 18/10 int.+ext.
Insulation thickness	60 (polyur. mm)
Doors number	1
Door type	Fully Insulated
Refrigeration type	Ventilated
Refrigerant type	ISCEON 89
Temperature range	-25° -30°
Temperature control/ adjustment	ECT-F Control: with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz
Capacity (LT)	700
Shelves nr.	suggested 3
Width (cm)	72
Depth (cm)	86
Height (cm)	208
Net weight (kg)	150
Equipment in accordance with	Directives 98/37/CE, 2006/95/CE, 2004/108/CE, 93/42/CE and following modifications
Internal cabinet with shelves/drawers interchangeable	



Accessories

- Additional open wire shelf realized in sheet steel plastic coated
- Drawer realized in aluminium
- Safety key locking
- Kit of castors with brakes
- Pt100 sensor
- WEB LIGHT SERVER (Rete Ethernet + GSM)
- GSM Communicator CF2008 module
- Interchange Rack System for Shelves/Baskets
- Internal steel wire basket
- Automatic water evaporation tray
- Frequency 60Hz
- Voltage 115V
- DMLP Digital Monitor (Alarm System)
Accessories for DMLP Digital Monitor:
 - DMLP Printer (Graphic Temp. Printer)
 - DMLP Remote panel
 - Ext. terminal board for RS485/dry contacts
 - DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output