

PINGU Twin 1500



Characteristics	
Structure	White version or Stainless steel 18/10 int. +ext.
Insulation thickness	70 (polyur. mm)
Doors number	2
Door type	Glass
Refrigeration type	Ventilated
Refrigerant type	R404A
Temperature range	+4°
Temperature control/ adjustment	ECT-F Control®: with Hi/Low Temp. alarm, door ajar, ON/OFF w/password
Defrosting type	Auto
Voltage	230V/1/50Hz ; 220V/1/60Hz
Capacity (LT)	1500
Internal lighting	Standard fitted
DMLP Digital monitor (Alarm system)	Standard fitted: - Back up battery (in case of power failure) - Temperature tracking with SD card incl. download interf. SW (memory of all temp Values and operation data, min 5 years) - 2 output relays (dry contact)
DMLP Printer (Graphic recorder)	Standard fitted
Drawers nr.	14
Storage capacity (blood bags nr., 450 ml)	672
Dimensions (cm)	144 x 82 x 205
Net weight (kg)	210
Equipment in accordance with	ECC directives nr. 73/23/ECC, 89/336/ECC, 89/109/ECC - Norm nr. CEI EN 61010-1 (CEI 66/5)
Available also with fully insulated door. Automatic water evaporation.	



Accessories

- Safety key locking
- Drawer perspex front (H=83 mm)
- Voltage 115V
- Frequency 60Hz
- Pt100 sensor
- DMLP remote panel
- Ext. Terminal board for RS485/dry contacts
- Probe for liquid simulation
- DMLP extension module + 1 PT100 + 4-20mA output
- Web light server module (Ethernet)
- GSM communicator module