

## Refrigerator LABO 1500



### Characteristics

Structure	White version or Stainless steel 18/10 int.+ext.	
Insulation thickness	60 (polyur. mm)	
Doors number	2	
Door type	Fully Insulated	
Refrigeration type	Ventilated	
Refrigerant type	R404A	
Temperature range	0° +15°	
Temperature control/ adjustment	ECT/F Control: Door alarm, Temperature alarm, Dirty Condenser alarm, faulty condenser, Faulty evaporator, faulty sensor, RS485 In/Out, Memory of last 12 alarms	
Defrosting type	Auto	
Voltage	230V/1/50Hz	220V/1/60Hz
Capacity (LT)	1500	
Internal lighting	Standard fitted	
Shelves nr.	Suggested 6	
Dimensions (cm)	144 x 82 x 205	
Net weight (kg)	170	
Internal cabinet with shelves / drawers interchangeable		
Automatic condensate water evaporation		

### Accessories

- Additional open wire shelf realized in sheet steel plastic coated
  - Drawer realized in aluminium
  - Safety key locking
  - Kit of castors with brakes
  - Cabel port
  - Inner electrical sockets
  - Humidity measuring sensor
  - Internal steel wire basket
  - Pt100 sensor
  - Frequency 60Hz
  - Voltage 115V
  - DMLP Digital Monitor (Alarm System)®
- Accessories for DMLP Digital Monitor®:
- DMLP Printer (Graphic Temp. Printer)
  - DMLP Remote panel
  - Ext. terminal board for RS485/dry contacts
  - DMLP PT100 Extension module + nr.1 PT100 + 4-20mA output
  - WEB LIGHT SERVER module (Ethernet)
  - GSM Communicator CF2008 module